

**213.3233**

**PLUG**  
**32A 2P+E 6h 200-250V 60Hz 50Hz**  
**Screw terminals**



EN 60309-1 (1999)  
 EN 60309-2 (1999)  
 EN 60309-1/A1 (2007)  
 EN 60309-1/A2 (2012)  
 EN 60309-2/A1 (2007)  
 EN 60309-2/A2 (2012)  
 Low voltage direct. 2014/35/EU

**■ GENERAL CHARACTERISTICS**

Commercial Series	OPTIMA Series
Synthetical description	PLUG
Mounting version	PORTABLE

**■ TECHNICAL CHARACTERISTICS**

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

**■ PHYSICAL CHARACTERISTICS**

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

**■ DOWNLOAD**

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)

**■ OPTIONS & VARIOUS NOTES**

Catalogue notes                      Version also available in black; just add ".K" at the end of the catalogue number.