

590.PL004004**NO CONTACT**

Switch size 63A Y2 GREEN 16A
690V~ - 6A 230V~ AC15 GW 960°C



* Product image may be indicative



EN 60947-5-1(2017)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	COMMAND Series
Synthetical description	NO CONTACT

■ TECHNICAL CHARACTERISTICS

Switch size	Y2
-------------	----

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Installation temperature	-25°C/+60°C
Colour	GREEN
GLOW WIRE	GW 960°C

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[STP\]](#)
[Technical drawing \[DWG\]](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Notes	16A 690V~ - 6A 230V~ AC15
Catalogue notes	NO=Normally open
	Snap catch

590.PL004002**NO CONTACT**

Switch size 16-32A Y1 D1 F1 GREEN
16A 690V~ - 6A 230V~ AC15 GW
960°C



* Product image may be indicative



EN 60947-5-1(2017)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	COMMAND Series
Synthetical description	NO CONTACT

■ TECHNICAL CHARACTERISTICS

Switch size	Y1
	D1
	F1

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Installation temperature	-25°C/+60°C
Colour	GREEN
GLOW WIRE	GW 960°C

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Notes	16A 690V~ - 6A 230V~ AC15
Catalogue notes	Snap catch
	NO=Normally open

590.PL004003**NC CONTACT**

Switch size 63A Y2 RED 16A 690V~ -
6A 230V~ AC15 GW 960°C



* Product image may be indicative



EN 60947-5-1(2017)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	COMMAND Series
Synthetical description	NC CONTACT

■ TECHNICAL CHARACTERISTICS

Switch size	Y2
-------------	----

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Installation temperature	-25°C/+60°C
Colour	RED
GLOW WIRE	GW 960°C

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Notes	16A 690V~ - 6A 230V~ AC15
Catalogue notes	NC=Normally closed
	Snap catch

590.PL004001**NC CONTACT**

Switch size 16-32A Y1 D1 F1 RED 16A
690V~ - 6A 230V~ AC15 GW 960°C



* Product image may be indicative



EN 60947-5-1(2017)

Low voltage direct. 2014/35/EU
DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	COMMAND Series
Synthetical description	NC CONTACT

■ TECHNICAL CHARACTERISTICS

Switch size	Y1
	D1
	F1

■ PHYSICAL CHARACTERISTICS

Material	THERMOPLASTIC
Installation temperature	-25°C/+60°C
Colour	RED
GLOW WIRE	GW 960°C

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

■ OPTIONS & VARIOUS NOTES

Notes	16A 690V~ - 6A 230V~ AC15
Catalogue notes	Snap catch
	NC=Normally closed