

תקע תעשייתי נייד




תק"ט pls-4010316

תקע נייד P-013 220-240V IP44 3X16A

Current(A):16A
Voltage (V) : 220-240V
Protection degree:IP44



2P+E



Earth contact position Rated current(A) Pole		6h	
		16	32
		3	
Dimension(mm)	a	122	141
	b	57	77
	c	50	64
	φ	6	8
Cable nominal cross-section area(mm ²)		1-2.5	2.5-6




תק"ט pls-4010332

תקע נייד P-023 220-240V IP44 3X32A

Current(A): 32A
Voltage (V) : 220-240V
Protection degree:IP44



2P+E



Earth contact position Rated current(A)		6h	
		16	32
Pole		3	
Dimension(mm)	a	122	141
	b	57	77
	c	50	64
	φ	6	8
Cable nominal cross-section area(mm ²)		1-2.5	2.5-6




תק"ט pls-4010416

תקע נייד P-014 380-415V IP44 4X16A

Current(A):16A
Voltage (V) : 380-415V
Protection degree:IP44



3P+E



Earth contact position Rated current(A)		6h	
		16	32
Pole		4	
Dimension(mm)	a	122	141
	b	64	77
	c	50	64
	φ	6	8
Cable nominal cross-section area(mm ²)		1-2.5	2.5-6




תק"ט pls-4010432

תקע נייד P-024 380-415V IP44 4X32A

Current(A): 32A
Voltage (V) : 380-415V
Protection degree:IP44



3P+E



Earth contact position Rated current(A) Pole		6h	
		16	32
		4	
Dimension(mm)	a	124	146
	b	49.5	57
	c	6-15	10-20
	sw	38	50
Cable nominal cross-section area(mm ²)		1-2.5	2.5-6




תק"ט pls-4010516

תקע נייד P-015 220-415V IP44 5X16A

Current(A):16A
Voltage (V) : 220-380V
240-415V
Protection degree:IP44



3P+N+E



Earth contact position Rated current(A) Pole		6h	
		16	32
		5	
Dimension(mm)	a	130	144
	b	75	87
	c	64	70
	φ	8	8
Cable nominal cross-section area(mm ²)		1-2.5	2.5-6