

תקע תעשייתי נייד




תק"ט pls-4010532

תקע נייד P-025 220-415V IP44 5X32A

Current(A): 32A
Voltage (V) : 220-380V
240-415V
Protection degree: IP44



3P+N+E



Earth contact position Rated current(A)	6h	
	16	32
Pole	5	
Dimension(mm)	a	130
	b	75
	c	64
	φ	8
	φ	8
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6



תק"ט pls-4015316


IP67

תקע נייד P-0132 220-240V IP67 3X16A

Current(A): 16A
Voltage (V) : 220-240V
Protection degree: IP67



2P+E



Earth contact position Rated current(A)	6h	
	16	32
Pole	3	
Dimension(mm)	a	118
	b	43.5
	c	6-15
	sw	38
	sw	50
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6



תק"ט pls-40150516


IP67

תקע נייד P-0152 220-415V IP67 5X16A

Current(A): 16A 32A
Voltage (V) : 220-380V
240-415V
Protection degree: IP67



3P+N+E



Earth contact position Rated current(A)	6h	
	16	32
Pole	5	
Dimension(mm)	a	133
	b	56
	c	8-16
	sw	42
	sw	50
Cable nominal cross-section area(mm ²)	1-2.5	2.5-6



תק"ט pls-40150563


IP67

תקע נייד P-035 220-415V IP67 5X63A

Current(A): 63A
Voltage (V) : 220-380V
240-415V
Protection degree: IP67



3P+N+E



Earth contact position Rated current(A)	6h	
	63	125
Pole	5	
Dimension(mm)	a	231.5
	b	110
	c	16-38
	φ	110
	φ	123
Cable nominal cross-section area(mm ²)	6-16	16-50



תק"ט pls-40155125


IP67

תקע נייד P-045 220-415V IP67 5X125A

Current(A): 125A
Voltage (V) : 220-380V
240-415V
Protection degree: IP67



3P+N+E



Earth contact position Rated current(A)	6h	
	63	125
Pole	5	
Dimension(mm)	a	231.5
	b	110
	c	16-38
	φ	110
	φ	123
Cable nominal cross-section area(mm ²)	6-16	16-50