

Acti9 iIL Three-phase voltage indicator light - Red - 230-400 Vac

A9E18327

Main

range of product	Acti9	
product name	Acti9 ilL	
Product or component type	Modular pilot light	
Device short name	ilL	
[Us] rated supply voltage	230400 V AC at 50/60 Hz	

Complementary

indicator light	3 LEDs red, service life 100000 h of constant lighting efficiency (consumption 0.9 W)	
Mounting mode	Fixed	
Mounting support	Symmetrical DIN rail	
Comb busbar and distribution block compatibility	Upside: ProDis	
9 mm pitches	2	
Height	82 mm	
Width	18 mm	
Depth	69.5 mm	
Colour	White (RAL 9003)	
Auxiliary connection terminal	Tunnel type terminal 1 cable(s) rigid 0.5 mm² Tunnel type terminal 2 cable(s) rigid 2.5 mm² Tunnel type terminal 1 cable(s) flexible 0.5 mm² Tunnel type terminal 2 cable(s) flexible 2.5 mm² Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm²	
Wire stripping length	9 mm	
Tightening torque	1 N.m	

Environment

Standards	IEC 73 IEC 1000-4
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-4080 °C

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	1.700 cm
Package 1 Length	6.800 cm
Package 1 Weight	48.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.000 cm
Package 2 Width	9.700 cm
Package 2 Length	23.200 cm
Package 2 Weight	631.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	6.372 kg

Contractual warranty

Warranty 12 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant with Exemptions	
SCIP Number	474a0055-af30-4dc1-84e3-b73fec311c07	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins