

Product datasheet

Specifications



Acti9 VDIS 3PN 125A 250/440V 66 connection points distribution block

A9XPK714

Main

Range	Acti9
product name	Acti9 VDIS
Product or component type	Vertical distribution block
Range compatibility	Pragma Prisma G Prisma Pack 250 Prisma Pack 160 PrismaSeT S

Complementary

Poles description	3P + N
[In] rated current	125 A
[Ue] rated operational voltage	250/440 V
Network type	AC
Network frequency	50/60 Hz
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of terminal blocks	1 with 66 outgoers
Connections - terminals	Supply: tunnel type terminals10...35 mm ² Distribution: push-in spring terminals1.5...10 mm ² (rigid) Distribution: push-in spring terminals4...16 mm ² (stranded) Distribution: push-in spring terminals1.5...16 mm ² (flexible) Distribution: push-in spring terminals1.5...16 mm ² (flexible with ferrule)
Distribution block outgoers	14 holes for per phase 24 holes for neutral
pollution degree	3
Height	680 mm
Depth	71.5 mm
Width	40.5 mm
Net weight	2.04 kg

Environment

IP degree of protection	IPxx B
-------------------------	--------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	5.300 cm
Package 1 Width	9.500 cm
Package 1 Length	73.000 cm
Package 1 Weight	2.182 kg
Unit Type of Package 2	P06
Number of Units in Package 2	54
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	132.000 kg


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins