

# Product data sheet

## Characteristics

### LV426403

circuit breaker Compact NSXm 40A 3P 50kA at 380/415V(IEC) EverLink lug



#### Main

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                                                                                                                                                                                                                                |
| Product name                                         | ComPact NSXm                                                                                                                                                                                                                                                                                                                                                                           |
| Range of product                                     | ComPact NSXm                                                                                                                                                                                                                                                                                                                                                                           |
| Device short name                                    | NSXm 40N                                                                                                                                                                                                                                                                                                                                                                               |
| Product or component type                            | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                        |
| Device application                                   | Distribution Protection                                                                                                                                                                                                                                                                                                                                                                |
| Number of poles                                      | 3P                                                                                                                                                                                                                                                                                                                                                                                     |
| Protected poles description                          | 3D                                                                                                                                                                                                                                                                                                                                                                                     |
| [In] rated current                                   | 40 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                          |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                      |
| Network type                                         | AC                                                                                                                                                                                                                                                                                                                                                                                     |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                               |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                       |
| Utilisation category                                 | Category A                                                                                                                                                                                                                                                                                                                                                                             |
| [Icu] rated ultimate short-circuit breaking capacity | 90 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>25 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>15 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 KA Icu at 600...690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | N 50 kA 415 V AC                                                                                                                                                                                                                                                                                                                                                                       |
| Trip unit name                                       | TM-D                                                                                                                                                                                                                                                                                                                                                                                   |
| Trip unit technology                                 | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                       |
| Trip unit protection functions                       | LI                                                                                                                                                                                                                                                                                                                                                                                     |
| Control type                                         | Toggle                                                                                                                                                                                                                                                                                                                                                                                 |
| Circuit breaker mounting mode                        | By screws<br>Clip-on                                                                                                                                                                                                                                                                                                                                                                   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company and is not intended to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

|                                                           |                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                             | 800 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                               |
| [Uimp] rated impulse withstand voltage                    | 8 kV                                                                                                                                                                                                                                                                                                                                                            |
| [Ics] rated service short-circuit breaking capacity       | 90 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>25 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>15 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>2.5 kA at 660...690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                                     | 20000 cycles                                                                                                                                                                                                                                                                                                                                                    |
| Electrical durability                                     | 10000 Cycles at 440 V In<br>20000 Cycles at 440 V In/2<br>5000 Cycles at 690 V In<br>10000 cycles at 690 V In/2                                                                                                                                                                                                                                                 |
| Mounting support                                          | Plate<br>DIN rail                                                                                                                                                                                                                                                                                                                                               |
| Connection terminals                                      | 1 Everlink lug wire size 2.5...95 mm <sup>2</sup> , rigid or stranded aluminium/copper<br>1 Everlink lug wire size 2.5...70 mm <sup>2</sup> , flexible copper                                                                                                                                                                                                   |
| Connection pitch                                          | 35 Mm with spreaders<br>27 mm without spreaders                                                                                                                                                                                                                                                                                                                 |
| 9 mm pitches                                              | 9 module                                                                                                                                                                                                                                                                                                                                                        |
| Protection type                                           | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic)                                                                                                                                                                                                                                                                            |
| Trip unit rating                                          | 40 A at 40 °C                                                                                                                                                                                                                                                                                                                                                   |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable                                                                                                                                                                                                                                                                                                                                                      |
| [Ir] long-time protection pick-up adjustment range        | 0.7...1 x In                                                                                                                                                                                                                                                                                                                                                    |
| Long-time protection delay adjustment type tr             | Fixed                                                                                                                                                                                                                                                                                                                                                           |
| [Im] magnetic protection pick-up range                    | 600 A                                                                                                                                                                                                                                                                                                                                                           |
| Earth-leakage protection                                  | Without                                                                                                                                                                                                                                                                                                                                                         |
| Number of slots for electrical auxiliaries                | 1 slot(s) for auxiliary switch OF<br>1 slot(s) for alarm switch SD<br>1 slot(s) for voltage release MN or MX                                                                                                                                                                                                                                                    |
| Width (W)                                                 | 81 mm                                                                                                                                                                                                                                                                                                                                                           |
| Height (H)                                                | 137 mm                                                                                                                                                                                                                                                                                                                                                          |
| Depth (D)                                                 | 80 mm                                                                                                                                                                                                                                                                                                                                                           |
| Net weight                                                | 1.06 kg                                                                                                                                                                                                                                                                                                                                                         |
| Colour                                                    | Grey (RAL 7016)                                                                                                                                                                                                                                                                                                                                                 |

## Environment

|                                       |                                                            |
|---------------------------------------|------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                               |
| Product certifications                | CCC<br>EAC<br>Marine                                       |
| Pollution degree                      | 3 conforming to IEC 60664-1                                |
| IP degree of protection               | IP40 conforming to IEC 60529                               |
| IK degree of protection               | IK07 conforming to IEC 62262                               |
| Ambient air temperature for operation | -25...70 °C                                                |
| Ambient air temperature for storage   | -50...85 °C                                                |
| Relative humidity                     | 0...95 %                                                   |
| Operating altitude                    | 0...2000 m without derating<br>2000...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 1.3 kg  |
| Package 1 Height             | 12.5 cm |
| Package 1 width              | 9 cm    |

|                              |          |
|------------------------------|----------|
| Package 1 Length             | 22 cm    |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 8        |
| Package 2 Weight             | 12.29 kg |
| Package 2 Height             | 30 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |