



Product data sheet

HDM6S250M1604XXX3

Characteristics

Molded case circuit breaker HDM6s - 250M 4P 160 A - adjustable - 40 C



Main

Range of product	HDM6s
Trip unit technology	Thermal-magnetic
Device application	Power distribution protection

Complementary

Product or component type	Enclosed moulded case circuit breaker
Poles description	4P
[In] rated current	160.0 A
Frame size	250AF
[Ue] rated operational voltage	400/415 V
Network type	AC
Network frequency	50...60 Hz
Electrical durability	1000.0 cycles
Mechanical durability	7000.0 cycles
[Uimp] rated impulse withstand voltage	8.0 kV
[Ics] rated service breaking capacity	30 kA
Rated breaking capacity	50 kA
[Ui] rated insulation voltage	800.0 V
Mounting mode	Adjustable
Height	142.0 mm
Width	165.0 mm
Depth	127.0 mm

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-20...70 °C
Operating altitude	0...2000 m
Standards	IEC 60947-2
Product certifications	CB CE KEMA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.