

Product data sheet

Characteristics

IMT47209

Mureva lights, Floodlight 20W 6500K, IP65
230V



Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	20 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	R _a =80
Luminous flux	2000 lm
Bulb lifespan	50000 h
Colour temperature	6500 K
Colour	Black
Beam angle	110 °
Shape	Rectangular
Height	163.4 mm
Width	121.4 mm
Depth	26.0 mm
Net weight	530 g

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
IK degree of protection	IK05
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	560 g
Package 1 Height	17.2 cm
Package 1 width	17.2 cm
Package 1 Length	17.2 cm
Unit Type of Package 2	S03

Number of Units in Package 2	20
Package 2 Weight	11.641 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Weight	198.256 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins