

Product data sheet

Characteristics

IMT47221

Mureva lights, Floodlight 50W 6500K, IP44 IR
Sensor 230V



Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	50 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	R _a =80
Luminous flux	5000 lm
Bulb lifespan	50000 h
Colour temperature	6500 K
Colour	Black
Provided equipment	Sensor
Beam angle	110 °
Shape	Rectangular
Height	215.4 mm
Width	221.4 mm
Depth	31 mm
Net weight	1.06 kg

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP44
IK degree of protection	IK04
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.2 kg
Package 1 Height	24.5 cm
Package 1 width	24.5 cm
Package 1 Length	24.5 cm

Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Weight	12.703 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Weight	113.624 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information