Specifications



Door, PrismaSeT XS, plain, white (RAL 9003), for enclosure 2 x 24 modules

LVSXDP224

Main

Range	PrismaSeT
Product or component type	Door
Accessory / separate part category	Enclosure accessory
Range compatibility	PrismaSeT XS

Complementary

Enclosure mounting	Flush Surface
Key number	Number to be stated
Door type	Plain
Door opening side	Right or left
Number of horizontal rows	2
9 mm pitches	48.0
Number of 18 mm modules per row	24
Total number of 18 mm modules	48.0
Net weight	3.840 kg
Enclosure material	Steel
Width	550 mm
Height	450 mm
Depth	20 mm
Colour	White (RAL 9003)
Market segment	Residential Small buildings

Environment

IP degree of protection	IP40
IK degree of protection	IK09
Ambient air temperature for operation	-2560 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	7.000 cm
Package 1 Width	54.000 cm
Package 1 Length	64.000 cm
Package 1 Weight	3.229 kg
Unit Type of Package 2	P12
Number of Units in Package 2	31
Package 2 Height	116.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	115.000 kg

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	24
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

igodoldoldoldoldoldoldoldoldoldoldoldoldol	
Circularity Profile	No need of specific recycling operations
Take-back	No