

Product datasheet

Specifications



Door, PrismaSeT XS, transparent, colourless, for enclosure 3 x 24 modules

LVSXDT324

Main

Range	PrismaSeT
Product or component type	Door
Accessory / separate part category	Enclosure accessory
Range compatibility	PrismaSeT XS

Complementary

Enclosure mounting	Flush Surface
Key number	Number to be stated
Door type	Transparent
Door opening side	Right or left
Number of horizontal rows	3
9 mm pitches	48.0
Number of 18 mm modules per row	24
Total number of 18 mm modules	72.0
Net weight	4.460 kg
Enclosure material	Door: glass Edge: steel
Width	550 mm
Height	600 mm
Depth	20 mm
Colour	Colourless
Market segment	Residential Small buildings

Environment

IP degree of protection	IP40
IK degree of protection	IK09
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	6.800 cm
Package 1 Width	63.500 cm
Package 1 Length	69.200 cm
Package 1 Weight	4.820 kg
Unit Type of Package 2	P12
Number of Units in Package 2	20
Package 2 Height	117.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	110.000 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **27**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Pro-active compliance (Product out of EU RoHS legal scope)**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**