

Door, PrismaSeT XS, transparent, colourless, for enclosure 5 x 24 modules

LVSXDT524

Main

Range	PrismaSeT
Product or component type	Door
Accessory / separate part category	Enclosure accessory
Range compatibility	PrismaSeT XS

Complementary

-		
Enclosure mounting	Flush	
	Surface	
Key number	Number to be stated	
<u>-</u>		
Door type	Transparent	
Door opening side	Right or left	
Number of horizontal rows	5	
9 mm pitches	48.0	
	40.0	
Number of 18 mm modules per	24	
row		
Total number of 18 mm modules	120.0	
Net weight	8.090 kg	
Enclosure material	Door: gloop	
Eliciosure material	Door: glass	
	Edge: steel	
Width	550 mm	
Height	900 mm	
Donth	00	
Depth	20 mm	
Colour	Colourless	
Market segment	Residential	
-	Small buildings	

Environment

IP degree of protection	IP40
IK degree of protection	IK09
Ambient air temperature for	-2560 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	7.000 cm
Package 1 Width	64.000 cm
Package 1 Length	99.000 cm
Package 1 Weight	6.600 kg
Unit Type of Package 2	P12
Number of Units in Package 2	17
Package 2 Height	117.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	128.000 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	37
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No