# **Product datasheet**

Specifications



### SPD connection kit, PrismaSeT S-XS

LVSXK6

#### Main

Range	PrismaSeT	
Product or component type	Connection kit	
Accessory / separate part category	Connection accessory	
Range compatibility	PrismaSeT XS PrismaSeT S	

## Complementary

Enclosure mounting	Surface Flush	
[Ue] rated operational voltage	400415 V AC/DC 5060 Hz	
Quantity per set	Set of 1	
Height	76 mm	
Width	59 mm	
Depth	43 mm	
Net weight	300 g	
Colour	Anthracite grey (RAL 7016)	

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	10 cm
Package 1 Length	15 cm
Package 1 Weight	110 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.6 kg

### Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

$ \bigtriangledown \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! \! $	
--	--

Environmental Disclosure

Product Environmental Profile

#### Use Better

Materials and Substances		
Minimum percentage of recycled plastic content	70	
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

#### Use Again

€ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins