

**513.1653T**

**SURFACE MOUNTING SOCKET**  
**16A 2P+E 6h 200-250V 60Hz 50Hz**  
 Screw terminals



EN 60309-2/A1 (2007)  
 EN 60309-1 (1999)  
 EN 60309-2 (1999)  
 EN 60309-1/A1 (2007)

Low voltage direct. 2014/35/EU

Commercial Series

OPTIMA-TOP Series

Synthetical description

SURFACE MOUNTING SOCKET

Mounting version

SURFACE MOUNTING

### ■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

### ■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M20X1,5

### ■ DOWNLOAD

[Technical drawing \[PDF\]](#)  
[Technical drawing \[DWG\]](#)  
[Technical drawing \[STP\]](#)