

ZCKY14

Limit switch lever, Limit switches XC Standard, ZCKY, steel roller ball bearing mounted, -40...120 Â°C



Main

| | |
|----------------------------|---|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ |
| Associated head | ZCKE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return metal (ball bearing mounted) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -25...70 °C for standard environment -40...70 °C for low temperature 10...120 °C for high temperature |
| Ambient air temperature for storage | -40...70 °C standard environment -40...70 °C low temperature 10...120 °C high temperature |
| Environmental characteristic | Standard environment High temperature Low temperature |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.000 cm |
| Package 1 Width | 2.300 cm |
| Package 1 Length | 5.200 cm |
| Package 1 Weight | 28.000 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 100 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 3.102 kg |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|